

Construction Products Limited

SPONGING PLASTER

ACRYLIC CEMENT TEXTURING MEDIUM

CEMENTITIOUS TROWEL TEXTURE POWDER

DESCRIPTION: An acrylic polymer/cement mixed dry powder blend that features adhesion, low build curing and wet consistency necessary to routinely achieve bold, trowel applied texture effects as used extensively on fibrous cement, rendered polystyrene and cement plaster building exteriors.

- Water based for ease of use and cleanup.
- Extremely economical, and a favoured bold texture finish effect in both domestic and commercial building practice.

TYPICAL PROPERTIES:

Specific Gravity: 1.6 mixed

Packaging: 20 kg paper bags

Shipping Weight: 20 Kgs.

Shelf Life: Minimum 12 months.

Mix Ratio: Mix at rate of one bag 20 kg to approximately 6-7 litres of water - experiment to find the mix that suits.

Texture Spread Rate: Approximately 11 m² per bag mix in a single coat.

Appearance: Highly thixotropic wet mix, low gloss grey mass when cured.

Safety: Non-flammable. Wet material is alkaline - avoid eye and skin contact.

APPLICATION: Add **SPONGING PLASTER** powder to clean, potable water while stirring. Mechanically mix with heavy duty drill until uniform and flowing. Apply by steel trowel spreading to the aggregate thickness and finish with plastic or polystyrene float. Over uniform plaster surfaces one coat is sufficient. Over varying porosity surfaces such as **rigid** jointed fibrous cement sheet use either two coats of **SPONGING PLASTER**, or use a preliminary coat of **GRIT SEALER** to provide uniform trowel "grab".

IMPORTANT NOTE

This product as supplied by **Construction Products Limited** is warranted to conform to those physical properties listed in the Typical Properties section of this information sheet.

NOT FOR USE OVER FLEXIBLE FIBRE CEMENT SHEET JOINTING COMPOUNDS.

Otherwise the information presented including that on suggested areas and methods of use is in good faith only and is specifically without recommendation or guarantee as to particular suitability. It is the responsibility of the purchaser to satisfy itself that the product is both fit for the purpose intended and that their use of the product can and does achieve that purpose in any particular instance or condition. Usage rates are presented as an initial guide only and do not account for wastage or substrate or build variations.

Jan 04

© **Construction Products Limited**
